


Custom Built Thermocouple Sensors with Standard Plug

- Sensors made to meet your requirements
- Thermocouple types K, T, J, N and E available
- Sheath diameters from 1.5mm to 6mm
- Wide choice of sheath materials
- Calibration available, please contact us for details
- Generally shipped in 5 to 7 days or sooner



For mating standard sockets, please see page 65

IEC colours available on request

SECTION 1	Thermocouple Type	Temperature Range (continuous)
K	Nickel Chromium vs Nickel Aluminium	0°C to +1100°C
T	Copper vs Constantan	-185°C to +400°C
J	Iron vs Constantan	+50°C to +800°C
N	Nicrosil vs Nisil	0°C to +1200°C
E	Nickel Chromium vs Constantan	0°C to +800°C

SECTION 2	Sheath Material	Maximum Temperature
118	321 Stainless Steel (Types K, J, T & E)	800°C
125	310 Stainless Steel (Type K)	1100°C
176	Inconel 600 (Types K & N)	1100°C
114	Nicrobell D (Types K & N)	1250°C
156	Hastelloy X (Type K)	1220°C

SECTION 3	Sheath Diameter (mm)	Sheath Diameter (inches)
Standard Sizes	1.5mm	0.059"
	2.0mm	0.079"
	3.0mm	0.118"
	4.5mm	0.177"
	6.0mm	0.236"

SECTION 4	Types of Sensing Junction	
2I		INSULATED (2ID for a Duplex element)
2G		GROUNDED (2GD for a Duplex element)

SECTION 5	Termination
3P6	

SECTION 6	Optional Stainless Steel Adjustable Compression Fittings	
Dia.	1/4" BSPT	1/2" BSPT
1.5mm	ACF69S	—
3.0mm	ACF59S	ACF58S
4.5mm	ACF10S	ACF11S
6.0mm	ACF16S	ACF17S

For our full range of fittings, please see pages 72 and 73

Order Code - Example

Type No	Thermocouple Type (See section 1)	Sheath Length in mm	Sheath Material (See section 2)	Sheath Diameter (See section 3)	Sensing Junction (See section 4)	Termination (See section 5)	Compression Fitting (Optional, see section 6)
12	- K	- 450	- 118	- 6.0	- 2I	- 3P6	- ACF17S